

GRADE 2 TOUCH BAR EXIT DEVICE



SPECIFICATIONS

- Certification: ANSI A156.3 Grade 2
- Material: Extruded anodized aluminum push bar, stainless steel springs
- Latch: Stainless Steel, 3/4" throw - 5/8" deadlatch
- Backset: 2-3/4" Covers 161 prep, includes latch & strike filler plates
- Strike: Surface mounted for 5/8" stop with shim, double door strike available
- Projection: 2-1/2" - 1-7/8" dogged
- Stile: 4-1/4" minimum
- Handing: Reversible, non-handed
- Door Thickness: 1-3/4" standard
- Door Width: 36" (field adjustable to 30") or 48"
- Mounting Height: Recommended installation at 41" from finished floor to center line of push rail.
- Fasteners: Furnished with sheet metal and machine screws
- Cylinder: Rim included, all key trims cylinder included except PLED
- Dogging: 1/2 turn hex key
- Fire Rated: Available - please specify
- Finishes: Aluminum and Stainless Steel
- Limited warranty: 10 years

HOW TO ORDER

KROM - 7 5 0 0 R F 6 8 9 4

Diagram illustrating the product code structure:

- KROM - Brand
- 7 - Touch Bar
- 5 - Rim Type
- 0 - Function
- 0 - Finish
- R - Option
- F - Finish
- 6 - Function
- 8 - Finish
- 9 - Option
- 4 - Option

Item Number	Function	Finish	Option
7500R	Fire Rated (F)	Aluminum (689) Stainless Steel (630)	4 Feet, 48" (4)
Notes: Default 36"			